


MC700 Pluggable PCB Connector, Plug



DIMENSIONS/POSITIONS

DIMENSIONS/POSITIONS		MC700-250..C	MC700-254..C
間距	Pitch	2.50mm	2.54mm
位數	Poles	2 ~ 24Poles	2 ~ 24Poles
塑膠本體	Housing Material	PA 66	PA 66
彈片	Spring	Stainless Strip Steel	Stainless Strip Steel
導電夾片	Contact	Phosphor Bronze, Tin Plated	Phosphor Bronze, Tin Plated
電線線徑	Wire Size	20 ~ 28AWG	20 ~ 28AWG
剝線長度	Wire Strip Length	5mm ~ 6mm	5mm ~ 6mm
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C

TECHNICAL DATA

連接符合標準 Connection in acc. with standard EN-VDE			
額定電流 I _n	Nominal Current I _n	4A	4A
額定橫截面	Nominal Cross Section	0.5mm ²	0.5mm ²
最大負載電流	Maximum load current	4A	4A
絕緣材料	Insulating Material	PA	PA
阻燃等級,符合UL94 Inflammability class acc. to UL94		V0	V0
額定電壓,UL/CUL Nominal voltage, UL/CUL		150V	150V
額定電流,UL/CUL Nominal current, UL/CUL		4A	4A

