

# MA126 PCB Terminal Block, Modular

MA



## DIMENSIONS/POSITIONS

## MA126-500M

間距	Pitch	5.00mm
位數	Poles	2 ~ 3Poles
塑膠本體	Housing Material	PA 66
彈片	Spring	Stainless Strip Steel
端子	Contact	Brass, Tin Plated
螺紋	Screw Thread	M2.6, Steel, Zinc Plated
電線線徑	Wire Size	12 ~ 26AWG
剝線長度	Wire Strip Length	5mm ~ 6mm
PCB孔徑	PCB Hole Diameter	1.3mm
最大緊固扭矩	Tightening Torque, Max.	3.54 Lb-in
環境作業溫度	Operating Temperature	-40°C to +105°C

## TECHNICAL DATA

連接符合標準 Connection in acc. with standard EN-VDE		
額定電流 I <sub>n</sub> Nominal Current I <sub>n</sub>	15A	
額定橫截面 Nominal Cross Section	-	
最大負載電流 Maximum load current	15A	
絕緣材料 Insulating Material	PA	
阻燃等級,符合UL94 Inflammability class acc. to UL94	V0	
額定電壓,UL/CUL Nominal voltage, UL/CUL	300V	
額定電流,UL/CUL Nominal current, UL/CUL	15A	

