


# MA524 PCB Terminal Block, Modular




## DIMENSIONS/POSITIONS

## MA524-500M

間距	Pitch	5.00mm
位數	Poles	2 ~ 3Poles
塑膠本體	Housing Material	PA 66
彈片	Spring	Brass, Stainless Steel
端子	Contact	Stainless Steel
螺紋	Screw Thread	M2.0, Steel, Zinc Plated
電線線徑	Wire Size	14~22AWG
剝線長度	Wire Strip Length	4mm ~ 5mm
PCB孔徑	PCB Hole Diameter	1.3mm
最大緊固扭矩	Tightening Torque, Max.	4.0 Lb-in
環境作業溫度	Operating Temperature	-40°C to +105°C

## TECHNICAL DATA

連接符合標準	Connection in acc. with standard EN-VDE	
額定電流 $I_n$	Nominal Current $I_n$	16A
額定橫截面	Nominal Cross Section	-
最大負載電流	Maximum load current	16A
絕緣材料	Insulating Material	PA
阻燃等級,符合UL94	Inflammability class acc. to UL94	V0
額定電壓,UL/CUL	Nominal voltage, UL/CUL	300V
額定電流,UL/CUL	Nominal current, UL/CUL	16A



Note:

Screw Plating: Changes are available upon request